

FTG12-50Ah 12V50Ah


Valve Regulated Lead Acid Battery




Specifications

| | | |
|-----------------------|------------------------|---------------------|
| Nominal voltage | 12V (6 cells per unit) | |
| Rated capacity (10HR) | 50Ah/10.8V | |
| Dimensions | Length | 277±2mm (10.91inch) |
| | Width | 106±2mm (4.17inch) |
| | Height | 221±2mm (8.70inch) |
| | Total height | 221±2mm (8.70inch) |
| Approx. weight | 16.00kg (35.30lbs)±3% | |

Outer dimensions (mm)



Terminal type (mm)



Characteristics

| | | |
|-------------------------------------------|-----------------------------------------|----------------------------------------------------------|
| Capacity (25°C) | 10HR (10.8V) | 50Ah |
| | 3HR (10.8V) | 36Ah |
| | 1HR (10.5V) | 26Ah |
| Terminal type | | T14 |
| Internal resistance (Fully charged, 25°C) | | Approx. 8mΩ |
| Capacity affected by temperature (10HR) | 40°C | 102% |
| | 25°C | 100% |
| | 0°C | 85% |
| | -15°C | 65% |
| Self-discharge (25°C) | 3 months | Remaining capacity: 91% |
| | 6 months | Remaining capacity: 82% |
| | 12 months | Remaining capacity: 65% |
| Nominal operating temperature | | 25°C±3°C (77°F±5°F) |
| Operating temperature range | Discharge | -15°C~50°C (5°F~122°F) |
| | Charge | -10°C~50°C (14°F~122°F) |
| | Storage | -20°C~50°C (-4°F~122°F) |
| Float charging voltage (25°C) | | 13.50 to 13.80V Temperature compensation: -18mV/°C/Block |
| Cyclic charging voltage (25°C) | | 14.40 to 14.70V Temperature compensation: -30mV/°C/Block |
| Maximum charging current | | 10A |
| Maximum discharge current | | 400A (5 sec.) |
| Design life | 12 years for floating (25°C) | |
| | Eurobat (20°C): 10-12 years, long life. | |

Construction

| Component | Positive plate | Negative plate | Container | Cover | Separator | Electrolyte | Safety valve | Terminal |
|--------------|----------------|----------------|-----------|-------|-----------|-------------|--------------|----------|
| Raw material | Lead dioxide | Lead | ABS | ABS | AGM | Gel | Rubber | Copper |

Constant current discharge characteristics unit: Ampere/Block (at 25°C, 77°F)


| F.V/Time | 10min | 15min | 30min | 60min | 2h | 3h | 4h | 5h | 8h | 10h | 20h |
|----------|-------|-------|-------|-------|------|------|------|------|------|------|------|
| 9.60V | 95.6 | 78.4 | 47.5 | 29.4 | 18.3 | 13 | 10.2 | 8.67 | 6.12 | 5.09 | 2.70 |
| 9.90V | 92.7 | 76.5 | 46.6 | 29.0 | 18.2 | 12.9 | 10.1 | 8.62 | 6.08 | 5.08 | 2.69 |
| 10.2V | 88.9 | 73.7 | 45.2 | 28.2 | 18.0 | 12.8 | 10.1 | 8.56 | 6.04 | 5.07 | 2.68 |
| 10.5V | 85.0 | 71.2 | 44.1 | 27.3 | 17.7 | 12.8 | 10.0 | 8.50 | 6.00 | 5.04 | 2.67 |
| 10.8V | 80.3 | 67.4 | 42.4 | 26.5 | 17.3 | 12.5 | 9.7 | 8.25 | 5.82 | 5.00 | 2.65 |

Constant power discharge characteristics unit: Watt/Block (at 25°C, 77°F)


| F.V/Time | 10min | 15min | 30min | 60min | 2h | 3h | 4h | 5h | 8h | 10h | 20h |
|----------|-------|-------|-------|-------|-----|-----|-----|------|------|------|------|
| 9.60V | 1032 | 861 | 533 | 335 | 212 | 153 | 120 | 102 | 72.7 | 60.8 | 32.4 |
| 9.90V | 1001 | 840 | 523 | 330 | 210 | 152 | 119 | 102 | 72.3 | 60.7 | 32.3 |
| 10.2V | 960 | 809 | 507 | 322 | 208 | 151 | 118 | 101 | 71.8 | 60.5 | 32.2 |
| 10.5V | 918 | 782 | 494 | 312 | 205 | 150 | 118 | 100 | 71.3 | 60.1 | 32.0 |
| 10.8V | 867 | 740 | 476 | 302 | 200 | 147 | 114 | 97.5 | 69.1 | 59.7 | 31.8 |

Note 1: Above characteristics data can be obtained within three charge and discharge cycles.


● Discharge characteristics (25°C)




● Charging characteristics (25°C)




● Temperature effects on capacity




● Self-discharge characteristics




● Floating life on temperature



● Cycle life on D.O.D (25°C)



● Relationship for OCV and capacity (25°C)



● Relationship for charging voltage and temperature

